

SS2 Series Specifications

| MECHANICAL (X & Y AXES) | |
|-------------------------|--------------------------|
| ANGLE OF MOVEMENT | 24° (12° EACH DIRECTION) |
| MECHANICAL LIFE CYCLES | 1 MILLION |
| CENTERING | SPRING RETURN |
| SWITCH MECHANISM | SNAP ACTION |
| LIMITER OPTIONS | 2 (-), 4 (+) or 8 (□) |
| MAX. VERTICAL LOAD | 80 lbF |
| MAX. HORIZONTAL LOAD | 22 lbF * |

* Measured 1.50" Above Panel Surface

| ELECTRICAL | |
|-------------------------|------------------------------|
| NUMBER OF SWITCHES | 2, 4, or 8 |
| SWITCH FUNCTION | MOMENTARY |
| NOMINAL CURRENT | SEE OPTIONS (5A STANDARD) |
| MAXIMUM VOLTAGE | 250VAC |
| CONTACT MATERIAL | SILVER |
| ELECTRICAL CONTACT LIFE | DEPENDENT ON LOAD (50K MIN.) |

| ENVIRONMENTAL | |
|------------------------|----------------|
| OPERATING TEMPERATURE | -10°F TO 185°F |
| STORAGE TEMPERATURE | -40°F TO 185°F |
| IP SEALING ABOVE PANEL | IP67 |

